

IN THE CLAIMS:

The text of all pending claims are set forth below. Cancelled and withdrawn claims are indicated with claim number and status only. The claims as listed below show added text with underlining and deleted text with ~~strike through~~. The status of each claim is indicated with one of (original), (currently amended), (previously presented), (cancelled), (withdrawn), (new), (previously added) and (not entered).

Please AMEND claims 1-5 and 11-15 and ADD new claims 22-25 in accordance with the following:

1. (CURRENTLY AMENDED) A coordinate input device having a polygonal wheel having plural sides, as a circumferential edge thereof, and which is rotatable about a first axis, comprising:

G1 cont
a plurality of rotating bodies, each of the rotating bodies disposed along a corresponding one of the plural sides and rotating along with ~~a the corresponding one of the plural sides~~ circumferential edge of said polygonal wheel about the first axis and each of the plurality of rotating bodies rotatable about the corresponding one of the plural sides said circumferential edge of said polygonal wheel as a second axis, ~~which is different from the first axis, each of the rotating bodies having an interior thereof with raised portions and recessed portions and the wheel having projections such that the rotating bodies, while rotating around the second axis, tactily communicate responsive to the rotation thereof;~~

rotating body rotating state detection means for detecting a rotating state of said rotating bodies;

wheel rotating state detection means for detecting a rotating state of said polygonal wheel;

a format change-over switch; and

data transmission means for transmitting information detected by each of said respective detection means as a set of operation instructions for a computer and adapted to effect transmission in a first format when said format change-over switch is not depressed and to effect another transmission in a second format when said format change-over switch is depressed.

2. (CURRENTLY AMENDED) A coordinate input device having a polygonal wheel having plural sides, as a circumferential edge thereof, and which is rotatable about a first axis, comprising:

a plurality of rotating bodies, each of the rotating bodies disposed along a corresponding one of the plural sides and rotating along with a the corresponding one of the plural sides ~~circumferential edge of said~~ polygonal wheel about the first axis and each of the plurality of rotating bodies rotatable about the corresponding one of the plural sides ~~said circumferential edge of said polygonal wheel~~ as a second axis, which is different from the first axis, ~~each of the rotating bodies having an interior thereof with raised portions and recessed portions and the wheel having projections such that the rotating bodies, while rotating around the second axis, tactilely communicate responsive to the rotation thereof;~~

ball moving state detection means for detecting a moving state of a ball;

click switch operating state detection means for detecting an operating state of a click switch;

wheel rotating state detection means for detecting a rotating state of said polygonal wheel;

a format change-over switch; and

data transmission means for transmitting respective pieces of information detected by said respective detection means as a set of operation instructions for a computer and adapted to effect transmission in a first format when said format change-over switch is not depressed and to effect another transmission in a second format when said format change-over switch is depressed.

3. (CURRENTLY AMENDED) The coordinate input device as set forth in claim 1, wherein said coordinate input device has a left click switch as a first switch and a right click switch as a second switch, said coordinate input device further comprising:

a third switch disposed as a lower portion of said polygonal wheel;

a wheel support portion having a construction to support said polygonal wheel and to allow said polygonal wheel to slide and adapted to drive said third switch by depressing said polygonal wheel downwardly; and

third switch operating state detection means for detecting the operating state of said third switch.

4. (CURRENTLY AMENDED) The coordinate input device as set forth in claim 3, wherein
said wheel support portion further comprises a ratchet construction on a side of said polygonal wheel, and wherein
said polygonal wheel is adapted to fit in said ratchet construction.

5. (CURRENTLY AMENDED) The coordinate input device as set forth in claim 1, wherein
an inner wall at a center of said respective rotating bodies through which said circumferential edge of said polygonal wheel is put has a locking construction, and wherein
said circumferential edge of said polygonal wheel is adapted to fit in a second locking construction.

6. (PREVIOUSLY PRESENTED) The coordinate input device as set forth in claim 1, wherein said rotating body is of a cylindrical configuration.

7. (PREVIOUSLY PRESENTED) The coordinate input device as set forth in claim 1, wherein said rotating body is of a spherical configuration.

8. (PREVIOUSLY PRESENTED) The coordinate input device as set forth in claim 1, wherein a surface of said rotating bodies is covered with a slip preventive material.

9. (PREVIOUSLY PRESENTED) The coordinate input device as set forth in claim 1, wherein a recess is formed in a surface of said rotating bodies.

10. (PREVIOUSLY PRESENTED) The coordinate input device as set forth in claim 1, wherein said coordinate input device further comprises:
ball moving state detection means for detecting a moving state of a ball; and
click switch operating state detection means for detecting an operating state of a click switch.

11. (CURRENTLY AMENDED) A coordinate input device having a polygonal wheel having plural sides, as a circumferential edge thereof, and which is rotatable about a first axis, comprising:

a plurality of rotating bodies, each of the rotating bodies disposed along a corresponding one of the plural sides and rotating along with a the corresponding one of the plural sides circumferential edge of said polygonal wheel about the first axis and each of the plurality of rotating bodies rotatable about the corresponding one of the plural sides said circumferential edge of said polygonal wheel as a second axis, which is different from the first axis, each of the rotating bodies having an interior thereof with raised portions and recessed portions and the wheel having projections such that the rotating bodies, while rotating around the second axis, tactilely communicate responsive to the rotation thereof;

rotating body rotating state detection means for detecting a rotating state of said rotating bodies;

a wheel rotating state detection unit detecting a rotating state of said polygonal wheel;

a format change-over switch; and

a data transmission unit transmitting information detected by each of said respective detection units as a set of operation instructions for a computer and adapted to effect transmission in a first format when said format change-over switch is not depressed and to effect another transmission in a second format when said format change-over switch is depressed.

12. (CURRENTLY AMENDED) A coordinate input device having a polygonal wheel having plural sides, as a circumferential edge thereof, and which is rotatable about a first axis, comprising:

G!
cont

a plurality of rotating bodies, each of the rotating bodies disposed along a corresponding one of the plural sides and rotating along with ~~a~~ the corresponding one of the plural sides ~~circumferential edge of said polygonal wheel~~ about the first axis and each of the plurality of rotating bodies rotatable about the corresponding one of the plural sides ~~said circumferential edge of said polygonal wheel~~ as a second axis, which is different from the first axis, ~~each of the rotating bodies having an interior thereof with raised portions and recessed portions and the wheel having projections such that the rotating bodies, while rotating around the second axis, tactily communicate responsive to the rotation thereof;~~

a rotating body rotating state detection unit detecting a rotating state of said rotating bodies;

a ball moving state detection unit detecting a moving state of a ball;

a click switch operating state detection unit detecting an operating state of a click switch;

a wheel rotating state detection unit detecting a rotating state of said polygonal wheel;

a format change-over switch; and

Grant
a data transmission unit transmitting respective pieces of information detected by said respective detection units as a set of operation instructions for a computer and adapted to effect transmission in a first format when said format change-over switch is not depressed and to effect another transmission in a second format when said format change-over switch is depressed.

13. (CURRENTLY AMENDED) The coordinate input device as set forth in claim 11, wherein said coordinate input device has a left click switch as a first switch and a right click switch as a second switch, said coordinate input device further comprising:

a third switch disposed as a lower portion of said polygonal wheel;

a wheel support portion to support said polygonal wheel and to allow said polygonal wheel to slide and adapted to drive said third switch by depressing said polygonal wheel downwardly; and

a third switch operating state detection unit detecting the operating state of said third switch.

14. (CURRENTLY AMENDED) The coordinate input device as set forth in claim 13, wherein said wheel support portion further comprises a ratchet construction on a side of said polygonal wheel, and wherein said polygonal wheel is adapted to fit in said ratchet construction.

15. (CURRENTLY AMENDED) The coordinate input device as set forth in claim 11, wherein an inner wall at a center of said respective rotating bodies through which said circumferential edge of said polygonal wheel is put has a locking construction, and wherein said circumferential edge of said polygonal wheel is adapted to fit in a second locking construction.

16. (PREVIOUSLY PRESENTED) The coordinate input device as set forth in claim 11, wherein said rotating body is of a cylindrical configuration.

17. (PREVIOUSLY PRESENTED) The coordinate input device as set forth in claim 11, wherein said rotating body is of a spherical configuration.

18. CANCELLED.

19. CANCELLED.

20. (PREVIOUSLY PRESENTED) The coordinate input device as set forth in claim 11, wherein a surface of said rotating bodies is covered with a slip preventive material.

21. (PREVIOUSLY PRESENTED) The coordinate input device as set forth in claim 11, wherein a recess is formed in a surface of said rotating bodies.

22. (NEW) A coordinate input device, comprising:

a plurality of rotating bodies;

a polygonal wheel having plural sides, the polygonal wheel being rotatable about a center thereof, as a first axis, each of the plural sides of the polygonal wheel couples to a respective one or ones of the plurality of rotating bodies such that each of the rotating bodies rotates with the corresponding one of the plural sides about the first axis, and is rotatable about the corresponding one of the plural sides of said polygonal wheel, as a second axis, which is different from the first axis; and

a processing unit to detect and to output at least one of a rotating state of the polygonal wheel and a respective one of the rotating bodies which is being rotated.

23. (NEW) The coordinate input device as set forth in claim 22, wherein each of the rotating bodies rotatably couples to only the corresponding one of the plural sides of the polygonal wheel.

Cl
cont

24. (NEW) A coordinate input device, comprising:

a plurality of rotating bodies;

a polygonal wheel having plural sides to rotate in a first direction, each of the rotating bodies being rotationally attached to a corresponding one of the plural sides to rotate in a second direction perpendicular to the first direction for multi-axial coordinate input; and

a processing unit to detect and to output at least one of a rotating state of the polygonal wheel and a respective one of the rotating bodies which is being rotated.

25. (NEW) A coordinate input device, comprising:

a polygonal wheel having rotating bodies thereon rotating in a direction perpendicular to a wheel rotation direction for multi-axial coordinate input; and

a processing unit to detect and to output at least one of a rotating state of the polygonal wheel and a respective one of the rotating bodies which is being rotated.